

Industrial Pressure Washers ...Built Right to Do the Job Right

SEA

Stationary, Electric-Powered, Cold Water Pressure Washer

- Up to 4.2 GPM
- Up to 3000 PSI
- Stainless Steel or Mild Steel Cabinet
- Accepts Hot Water *Up to 185°F*

■ Industrial-Grade Motor is connected to the rugged, class-leading, tri-plunger, oil-bath LT (stainless steel model) or LM (mild steel model) High-Pressure Pump (with 7-year warranty) by dual, V-cogged belts. Pulleys are made of cast iron and can be easily adjusted by turning two bolts.

Add portability to the SEA with optional Wheel Kit (stainless steel model #8.904-527.0 or mild steel model #9.801-031.0), including detergent jug holder. Optional Hose Reel (#8.903-521.0) provides tangle-free handling of up to 100 ft. of high-pressure hose.




■ Many Safety Features, including a thermal pump protector to prevent the buildup of excessive pressures or heat.

- SEA3-11024D
- Shown with stainless steel cabinet









■ 50 ft. of double steel-wire braid High Pressure Hose with 24-inch Hose Guard for burst protection and swivel crimp fitting for tangle-free handling of hose and trigger gun.

- Easy-to-attach **Detergent Injector** for easy application of soap.
- Helpful Tri-Lingual Labels with operating instructions in English, Spanish and French for added liability protection and operator convenience.
- Time-Delay Shutdown (stainless steel model only) automatically turns off unit, if not in use for a set time, for protection against unattended operation.
- Easily handles Water Up To 185°.
- With the switch in the 'ON' position, the optional Auto Start/Stop function allows the unit to be turned on with the pull of the trigger for convenient remote operation. (This option replaces Time-Delay Shutdown.)

- EASY!Force Trigger Gun with cruise control like technology uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use. Dual-lance Variable Pressure Wand make for easy cleaning and adjusting the pressure while washing.
- Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection (stainless steel model only and cannot be ordered with wheel kit option).
- 36 ft. of high-grade Electrical Cord with Ground Fault Circuit Interrupter (on single-phase models) for operator safety.
- Compact Design, 31" L x 21" W x 16" H.



SEA3-11024D Shown with mild steel cabinet www.landa.com



WHY CHOOSE THE SEA

This top-of-the-line stationary cold-water series features a heavy-duty stainless steel or mild steel cabinet and comes standard with an insulated variable pressure wand, 50' of hose, and time delay shutdown. Available options include our LanCom wireless remote control, floor stand, and wall mount bracket assembly. There is even an optional wheel kit for adding mobility, making an already top-quality machine even more flexible than before. This unit is ideal for cleaning a variety of indoor surfaces, and can be plumbed for plug-and-wash outdoor applications as well.

Model #	Part #	Cabinet	GPM	PSI	Pump RPM	Pump	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
SEA3-11024D	1.106-500.0	stainless steel	2.8	1000	1650	LB3030R	2.0	120	1	20	210
SEA4-20024A	1.106-501.0	stainless steel	4.2	2000	1450	LT6036R.2	6.2	230	1	28	280
SEA4-20024B	1.106-502.0	stainless steel	4.2	2000	1450	LT6036R.2	6.2	230	3	16	220
SEA4-20024C	1.106-503.0	stainless steel	4.2	2000	1450	LT6036R.2	6.2	460	3	7.2	220
SEA4-20024G	1.106-505.0	stainless steel	4.2	2000	1500	LT6036R.2	6.2	208	1	30	297
SEA4-20024H	1.106-506.0	stainless steel	4.2	2000	1450	LT6036R.2	6.2	208	3	18.5	220
SEA4-30024B	1.106-507.0	stainless steel	3.5	3000	1450	LT6036R.2	7.5	230	3	21.5	235
SEA4-30024C	1.106-508.0	stainless steel	3.5	3000	1450	LT6036R.2	7.5	460	3	10.5	305
					-						
SEA3-11024D	1.106-583.0	mild steel	2.8	1000	1650	LB3030R	2.0	120	1	20	275
SEA4-20024A	1.106-584.0	mild steel	4.2	2000	1500	LM4035R.3	6.2	230	1	29	275
SEA4-20024B	1.106-585.0	mild steel	4.2	2000	1500	LM4035R.3	6.2	230	3	11	275
SEA4-20024C	1.106-586.0	mild steel	4.2	2000	1500	LM4035R.3	6.2	460	3	11	275
SEA4-20024H	1.106-587.0	mild steel	4.2	2000	1500	LM4035R.3	6.2	208	3	16	275
SEA4-30024B	1.106-588.0	mild steel	3.5	3000	1500	LM4035R.3	7.5	230	3	19	275
SEA4-30024C	1.106-589.0	mild steel	3.5	3000	1500	LM4035R.3	7.5	460	3	11	275

Dimensions: 31"L x 21"W x 16"H

Field Installed Options & Accessories

9.801-036.0	Cox Hose Reel Kit (floor stand / wall mount)	Stainless St	eel Models
8.903-521.0	E-Zee Hose Reel & Mounting Kit (fits wheel kit)	8.930-163.0	LanCom W
9.802-265.0	Hose Reel, Mini, (fits wall bracket, 150' capacity)	8.930-177.0	LanCom W
8.711-860.0	Hose Reel, Mini, (fits wall bracket, 100' capacity)	8.903-461.0	Remote Or
9.801-035.0	Wheel Kit (4 casters) for Floor Stands	8.930-358.0	Additional
9.801-031.0	Wheel Kit with Detergent Rack	8.903-619.0	Wall Moun
8.903-040.0	24" Floor Stand	8.930-131.0	Wall Moun
9.801-034.0	36" Floor Stand	8.903-511.0	Auto Start
8.903-617.0	36" Floor Stand (stainless steel)	8.904-527.0	Wheel Kit

Stainless Steel Models Only

8.930-163.0 LanCom Wireless Remote Control, 1-Step Detergent • ○
8.930-177.0 LanCom Wireless Remote Control, 2-Step Detergent • ○
8.903-461.0 Remote On/Off Switch Option (Time Delay units only) • •
8.930-358.0 Additional LanCom Remote
8.903-619.0 Wall Mount Bracket Assembly
8.930-131.0 Wall Mount Bracket for Fixed LanCom Remote

.903-511.0 Auto Start/Stop (Replaces Time Delay Shutdown) • 0.904-527.0 Wheel Kit with Detergent Rack (stainless steel)*

8.903-448.0 Float Tank Option with Inlet Soap Injection ◆* ○

• Factory Installed * Float Tank cannot be ordered with Wheel Kit • Not compatible with LanCom • Not compatible with Auto Start/Stop or Float Tank options


DETERGENT FOR EVERY JOB



Landa Kärcher Group's innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.

Distributed by:

SPEED IT UP WITH ACCESSORIES



If you're cleaning long hours at a time, the EASY!Force trigger gun is an ideal and innovative solution to alleviate user fatigue. It's designed to use its own recoil force to hold the trigger down, which means you won't have sore hands after hours of use.

Give us a call to learn which accessories are suitable to use with your pressure washer and your application.



Mild Steel Models Only

9.801-013.0 Hour Meter •

9.801-011.0 Auto Start/Stop •*

9.801-012.0 Time Delay Shutdown •

9.801-033.0 Wall Mount Bracket Assembly